

LED TROFFER 2x2

Step1

Turn off the switch

Step2

Step3

Black — Black — Black
White — White — White
Ground Wire — Ground Wire

120V~277V SERVICE

Step4

Step5

36W	24W	20W
3000K	4000K	5000K

Step6

Step7

Step8

Turn on the switch

ON

Caution: Please note that DO NOT use this product in the following places/application

1. The place has a large quantity of lampblack and smoke, such as: kitchen and Food processing factory etc.
2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -15 and 45 degrees.

LED TROFFER 2x2

Step1

Turn off the switch

Step2

Step3

Black — Black — Black

White — White — White

Ground Wire — Ground Wire

} 120V~277V SERVICE

Step4

Step5

36W

24W

20W

3000K

4000K

5000K

Step6

Step7

Step8

Turn on the switch

ON

Caution: Please note that DO NOT use this product in the following places/application

1. The place has a large quantity of lampblack and smoke, such as: kitchen and Food processing factory etc.
2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -15 and 45 degrees.

LED TROFFER 2x2

Step1

Turn off the switch

Step2

Step3

Black — Black — Black
White — White — White
Ground Wire — Ground Wire

120V~277V SERVICE

Step4

Step5

36W	24W	20W
3000K	4000K	5000K

Step6

Step7

Step8

Turn on the switch

ON

Caution: Please note that DO NOT use this product in the following places/application

1. The place has a large quantity of lampblack and smoke, such as: kitchen and Food processing factory etc.
2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -15 and 45 degrees.

LED TROFFER 2x2

Step1

Turn off the switch

Step2

Step3

Black — Black — Black

White — White — White

Ground Wire — Ground Wire

} 120V~277V SERVICE

Step4

Step5

36W

24W

20W

3000K

4000K

5000K

Step6

Step7

Step8

Turn on the switch

ON

Caution: Please note that DO NOT use this product in the following places/application

1. The place has a large quantity of lampblack and smoke, such as: kitchen and Food processing factory etc.
2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -15 and 45 degrees.

LED TROFFER 2x2

Step1

Turn off the switch

Step2

Step3

Black — **Black** — **Black**

White — **White** — **White**

Ground Wire — **Ground Wire**

120V~277V SERVICE

Step4

Step5

36W

24W

20W

3000K

4000K

5000K

Step6

Step7

Step8

Turn on the switch

ON

Caution: Please note that DO NOT use this product in the following places/application

1. The place has a large quantity of lampblack and smoke, such as: kitchen and Food processing factory etc.
2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -15 and 45 degrees.

LED TROFFER 2x2

Step1

Turn off the switch

Step2

Step3

Black — Black — Black

White — White — White

Ground Wire — Ground Wire

120V~277V SERVICE

Step4

Step5

36W	24W	20W
3000K	4000K	5000K

Step6

Step7

Step8

Turn on the switch

ON

Caution: Please note that DO NOT use this product in the following places/application

1. The place has a large quantity of lampblack and smoke, such as: kitchen and Food processing factory etc.
2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -15 and 45 degrees.

LED TROFFER 2x2

Step1

Turn off the switch

Step2

Step3

Black — Black — Black

White — White — White

Ground Wire — Ground Wire

120V~277V SERVICE

Step4

Step5

36W	24W	20W
3000K	4000K	5000K

Step6

Step7

Step8

Turn on the switch

ON

Caution: Please note that DO NOT use this product in the following places/application

1. The place has a large quantity of lampblack and smoke, such as: kitchen and Food processing factory etc.
2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -15 and 45 degrees.

LED TROFFER 2x2

Step1

Turn off the switch

Step2

Step3

Black — Black — Black
White — White — White } 120V~277V SERVICE
Ground Wire — Ground Wire

Step4

Step5

36W	24W	20W
3000K	4000K	5000K

Step6

Step7

Step8

Turn on the switch

ON

Caution: Please note that DO NOT use this product in the following places/application

1. The place has a large quantity of lampblack and smoke, such as: kitchen and Food processing factory etc.
2. The place has a large quantity of chemical corrosive substance, such as: chemical plant and stockyard etc.
3. The place has poor temperature conditions, large-scale temperature variation, which would easily lead to broken and damage the product, the applicable operating temperature is between -15 and 45 degrees.