



Zhongshan Halcon Lighting & Electrical Co., Ltd

Add: Floor#2, Building D, YinCheng Industrial Park, No 9, ShunXing North Road, HengLan Town, ZhongShan, GD, China

Tel: 0086-760-87556293 87556292 87556295

Fax: 0086-760-87556294

Website: <http://www.halconlighting.com>

E-mail: emily@halconlighting.com

SPECIFICATION

SUSPENDED LED SURFACE MOUNT P1836



OFFICE/ ARCHTECTRUAL/ SCHOOL/DISPLAY CENTRES

it contributes to comfortable, healthy workplaces by lighting the task, face and space.

It produces soft light with no visible LEDs.

To complete the range, the recessed version is now joined by IQ Wave surface and suspended.

Available in 1200 mm and 1500 mm, they can be joined together in a continuous line, to create a sleek look.

It is available with lumen packages ranging from 2000 lm to 4000 lm, in colour temperatures of 3000K or 4000K

The surface mounting offers extra demanding for school applications.

The special optical design achieves high efficacy, and even more energy can be saved thanks to control options including presence/absence detection and daylight dimming

CONTROLS ■

Fixture can be equipped with an occupancy sensor.

Devices are factory-installed and require minimal labor to set up during fixture installation.

DIMMING ■

Drivers come standard with DALI Dimming version

FINISHES ■


Standard fixture is powder coated on surface



PRODUCT FEATURES ■

- * ETL & DLC listed; With LM79 & LM80;
- * 2ft:30w, 4ft: 40W, 5ft: 50W, 8ft: 60W
- * High luminous efficacy 80 LM/W;
- * 50,000 hours warranty Osram/Phillip/Tridonic/ Lifud LED Driver, flickering free.
- * PF>0.90
- * driver efficiency>87%;THD<20%;
- * Installation: Suspended,Flush mount.
- * Suitablefor dry/damp location;
- * Designed for office/ architectrual/ school/ display centres
- * CCT: 3000K,4000K & 5000K;
- * Lifetime: 5 years

PRODUCT DIMENSION ■





Model No	A	B	C
P1836-30W/2ft	23.85"	2.95"	1.69"
P1836-40W/4ft	23.85"	2.95"	1.69"
P1836-50W/5ft	47.48"	2.95"	1.69"
P1836-60W/8ft	59.84"	2.95"	1.69"



TECHNICAL DATA

Total Input Watt	30W	40W	50W	60W
SMD LED Chips Brand	2ft	4ft	5ft	6ft
Calculated L70	50,000hrs			
Delivered Lumens	2400 lm	3200 lm	4000 lm	4800 lm
Luminaire Efficacy Rating	80 LM/W			
Correlated Color Temperature	3000K,4000K,5000K			
Color Rendering Index	>80			

LIGHT DISTRIBUTION











INSTALLATION FOR HANGING

Installation Manual

Model No.:P1835

PENDANT LIGHT

<p>Step1</p>  <p>Turn off the switch</p>	<p>Step2</p>  <p>Mark fixing holes</p>
<p>Step3</p>  <p>Drill holes</p>	<p>Step4</p>  <p>Insert rawl plugs</p>
<p>Step5</p>  <p>Secure in place</p>	<p>Step6</p>  <p>appropriate strain relief device</p>
<p>Step7</p> <p>Turn on the switch</p>  <p>ON</p>	


Caution: Please note that DO NOT use this product in the following places/application

- 1.The place has a large quantity of lampblack and smoke,such as:kitchen and Food processing factory etc.
- 2.The place has a large quantity of chemical corrosive substance,such as:chemical plant and stockyard etc.
- 3.The place has poor temperature conditions,large-scale temperature variation ,which would easily lead to broken and damage the product,the applicable operating temperature is between-15 and 45 degrees.



APPLICATIONS ■

Office



Conference Room



PACKAGE/WEIGHT ■

Model No	Master Carton Size (LxWxH)	Qty/Carton (pcs)
P1836-30W/2ft	28.74"x10.63"x5.71"	5
P1836-40W/4ft	51.97"x10.63"x5.71"	5
P1836-50W/5ft	67.72"x10.63"x5.71"	5
P1836-60W/6ft	75.60"x10.63"x5.71"	5